

Double slope solar still with implementation of ZnO nanoparticles

Activated carbon

M.Venkateswarlu

Research Centre for Solar Energy, Department of Engineering Physics, College of Engineering, Koneru Lakshmaiah Education Foundation, Green Fields, Vaddeswaram, Guntur 522502, Andhra Pradesh, India. asangeetha29072021@gmail.com

Abstract

ACNP prepared by Mangifera Indica; Celostia Argentea doped with ZnO nanoparticles at various weight ratios 5; 10; 15; 20; and 25 wt%. They theoretically analyzed the function used with Gibbs free energy equation. Due to the novel materials and balls performance the still achieve the output of distillate 14.92 l/m² day and efficiency upto 38.73%. U shape is also a novel work in the design of the solar still with construct with vapor tight.

Introduction

Sharshir et al [1] experimentally investigated the stepped double slope solar still with linen wicks and carbon black nanoparticles they enhanced the evaporation surface area and internal heat transfer. It showed that distill water protectivity of the solar is still 80.57% and energy efficiency is 110.5%. Gamel et al [2] accomplished an experimental investigation to examine the energy and exergy efficiency with activated carbon tubes of solar still are enhanced by 94.14% and 164.29% respectively. They yield freshwater productivity is 5850 ml/m². T. Kumar et al [3] analyzed the SSSS with green synthesis material of SiO₂ with leaf extract of Jatropha curcas L. They compared result in summer and winter season performance solar still achieved the distillate yield of 8.79 L/day (SiO₂/Jatropha curcas L.) and 6.49 L/day (SiO₂). Adewumi et al [4] prepared the ZnO Rice Husk Activated Carbon with orthophosphoric acid activation. They analyzed the physicochemical parameters concluded that 615 m² g⁻¹ high surface area useful in wastewater treatment.




Fig.-1. Schematic view




Fig- 2. Experimental setup




Fig-3. Solar Intensity




Fig-4 Ambient temperature




Fig-5. Overall efficiency




Fig.-6. Efficiency comparison

Conclusion:

In the novel work the role of ACNP produce from ZMC enhance the heat transfer in the solar distiller then mixed with mat black paint coated in the basin area of the U shape. The 20% researcher achieved the high USB temperature upto 62 °C. Maximum of the instantaneous efficiency of 58.98% reached at 1 p.m. The sensible heat materials enhance the inside temperature produce the distillate output upto 14.92 l/m² day and higher performance of 64%.

Reference

- [1] Swellam W. Sharshir, Mohamed A. Eltawil, Almoataz M. Algazzar, Ravishankar Sathyamurthy, A.W. Kandeal. Performance enhancement of stepped double slope solar still by using nanoparticles and linen wicks: Energy, exergy and economic analysis. *Applied Thermal Engineering* 174 (2020) 115278. <https://doi.org/10.1016/j.applthermaleng.2020.115278>
- [2] T. Rajesh Kumar, S. Shanmugan, G. Sunita Sundari, N. S. M. P Latha Devi, N. Abhiram, G. Palanikumar. Experimental Investigation on the Performance of a Solar Still Using SiO₂ Nanoparticles /*Jatropha curcas* L. Silicon. <https://doi.org/10.1007/s12633-021-01119-y>
- [3] Hidouri, K., & Mohanraj, M. (2019). Thermodynamic analysis of a heat pump assisted active solar still. *Desalination and Water Treatment*, 154, 101-110.
- [4] Saba, S. S., Sreelakshmi, D., Kumar, P. S., Kumar, K. S., & Saba, S. R. (2020). Logistic regression machine learning algorithm on MRI brain image for fast and accurate diagnosis. *International Journal of Scientific and Technology Research*, 9(3), 7076-7081.